

東業德勤測試顧問有限公司
ETS-TESTCONSULT LIMITED

8/F., Block B, Veristrong Industrial Centre, 34-36 Au Pui Wan Street, Fotan, Hong Kong
Tel : 2695 8318 E-mail : etl@ets-testconsult.com
Fax : 2695 3944 Web site : www.ets-testconsult.com

TEST REPORT

Wai Kee (Zens) Construction & Transportation Co., Ltd.

**CONSTRUCTION OF JETTY
AT LUNG KWU CHAU**

(CED CONTRACT NO.: CV/2002/11)

**MONTHLY EM&A REPORT
(09 OCTOBER TO 08 NOVEMBER 2003)**

Prepared by: Linda Law
Linda Law
Environmental Officer

Checked by: C. L. Lau
C. L. Lau
Environmental Team Leader

Approved by: Tony Wong
Tony Wong
Operations Manager

Date: 09 October to 08 November 2003

Report No.: ENA 30537

AUES

Our Ref: TCS/2003/E010/600/Cert-07

INDEPENDENT ENGINEER AUDIT CERTIFICATE

CED CONTRACT NO. CV/2002/11

CONSTRUCTION OF LUNG KWU CHAU JETTY

ENVIRONMENTAL MONITORING AND AUDIT REPORT (9 OCTOBER - 8 NOVEMBER 2003)

We certify that this report has been audited against Environmental Permit No. EP-150/2002 A
using reasonable skill and care.

Signed:



(CLIFF LAM)

INDEPENDENT ENGINEER

Name: CLIFF LAM

**Action-United
Environmental Services & Consulting**

Date: 17 November 2003



TABLE OF CONTENTS

	Page
EXECUTIVE SUMMARY	
1.0 INTRODUCTION	1
2.0 PROJECT INFORMATION	1
2.1 Background	1
2.2 Project Location and Scope	1
2.3 Construction Programme	1
2.4 Project Organization and Management Structure	2
2.5 Contact Details of Key Personnel	2
3.0 CONSTRUCTION PROGRESS IN THIS REPORTING MONTH	2
4.0 MARINE WATER QUALITY MONITORING	
4.1 Monitoring Locations	3 – 4
4.2 Monitoring Parameters	4
4.3 Monitoring Frequency	4
4.4 Monitoring Methodology and Equipment Used	4
4.5 Quality Assurance (QA) / Quality Control (QC) results and Determination Limits	4 – 5
4.6 Details of site Equipment used for In-situ measurement	5
4.7 Action and Limit Level	5
4.8 Event-Action Plans	5
4.9 Monitoring Duration and Period	6
4.10 Marine Water Monitoring Results	6 – 7
4.11 Explanation of Exceedance	7
5.0 ECOLOGY MONITORING	
5.1 Introduction	7
5.2 Monitoring Procedure	7
5.3 Monitoring Frequency and Schedule	7
5.4 Result and Observation	7
6.0 ENVIRONMENTAL NON-CONFORMANCE	
6.1 Summary of environmental monitoring	7
6.2 Summary of environmental complaints	8
6.3 Summary of notification of summons and prosecutions	8
7.0 WASTE MANAGEMENT	
7.1 Waste Management Audit	8
7.2 Records of Waste Quantities	8
8.0 ENVIRONMENTAL AUDIT	
8.1 Site Inspection	8
8.2 Status of Environmental Licensing and Permitting	8
8.3 Implementation Status of Environmental Mitigation Measures	9
8.4 Recommendations on site inspection findings	9
8.5 Implementation Status of Event and Action Plan	9
8.6 Implementation Status of Environmental Complaint Handling	9
8.7 Implementation of Notification of Summons and Prosecution	9
9.0 CONCLUSION	9 – 10
10.0 FUTURE KEY ISSUES	
10.1 Upcoming EM&A Schedule	10
10.2 Upcoming construction works schedule in coming two month	10

APPENDIX

- A Organization Chart
- B1 Calibration Certificates of Impact Monitoring Equipments
- B2 Impact Monitoring Results
- C Graphical Plots of Impact Monitoring Data
- D Weather Condition during Impact Monitoring
- E Construction Programme of the Project
- F Event-Action Plans
- G QA/QC Results of Laboratory Analysis
- H Summary of Implementation Status of Mitigation Measures

FIGURE

- Figure 1 Construction of Lung Kwu Chau Jetty
- TS-2031 Proposed Marine Water Quality Monitoring Stations

	Page
TABLES	
2.1 Contact Details of Key Personnel	2
3.1 Implementation of Environmental Mitigation Measures	2
4.1 Marine Water Quality Monitoring Stations	3
4.2 Monitoring Parameters	3
4.3 Other relevant water quality parameters	3
4.4 Monitoring Frequency of Impact Monitoring	4
4.5 The Summary of laboratory testing method of total suspended solids	5
4.6 Details of Impact Monitoring Equipment (In-situ measurement)	5
4.7 Water Quality Action and Limit Levels	6
4.8 Time Schedule of Water Quality Monitoring at Lung Kwu Chau	6
4.9 Summary of Marine Water Quality Exceedances in this reporting month	7
4.10 Daily summary of record of marine water quality	7
7.1 Summary of Quantities of Waste for Disposal in this reporting month	8
7.2 Summary of Daily Dredging Volume in this reporting month	9
8.1 Summary of environmental licensing and permit status	9
10.1 Construction Plan in the coming two months	11



EXECUTIVE SUMMARY

This monthly EM&A report No.5 has been prepared by the Environmental Team (ET) of ETS-Testconsult Ltd for impact monitoring under the Environmental Permit No. EP-150/2002/A (the EP) for " Construction of Jetty at Lung Kwu Chau (CED Contract No.: CV/2002/11) " (The Project) during the reporting period from 09 October to 08 November 2003.

Construction Progress

The major construction works in this reporting month included the placing of sub-base at jetty and catwalk, setting of precast concrete pavings, setting of precast footpath's footing and slabs, in-situ concreting of staircase, copings and pavings, construction of pillar boxes, marine fitting and E&M installation, and placing of armour rock along catwalk.

Environmental Monitoring Progress

The monitoring activities in this monitoring month are summarized below:

- Marine water monitoring: 4 Occasions;
- Site inspection: 4 Occasions.

Marine Water Monitoring

One exceedance of Action Level in Turbidity at Monitoring Station M1 at 03/11/2003 (Mid-ebb) was recorded in this reporting month. During the marine water quality monitoring at 03/11/2003, ET found that the major construction works was demolishing existing pier. No visible foam, oil, grease, litter or other objectionable matter were observed near the monitoring stations. Comparing the monitoring results of the same tide, the turbidity at M1 was lower than 120% of upstream control station C1. Besides, the Turbidity result at monitoring station M2 which is closer to the existing pier was found lower than monitoring station M1 and within the Action and Limit Level. This concluded that the water quality impact due the construction works was low and did not cause adversely effect on water quality near the site. Therefore, the exceedance was not work-related.

Site Inspection

Environmental audits and inspections conducted in this reporting month are summarized as follows:

<u>Concerned Parties</u>	<u>Dates of Audit / Inspection</u>
CED / WKC&T / ET	17/10, 24/10, 31/10, 7/11

The Contractor was recommended to maintain good environmental management in order to minimize environmental impacts at the site.

Environmental Complaints and Notification of Summons and Successful Prosecutions

No environmental complaints were received and no notification of summons and prosecutions with respect to environmental issues were registered in this reporting month.

Future Key Issues and Recommendations to the Contractor

The Contractor is recommended to minimize the environmental impacts through maintenance of good site practice and implementation of the required waste management.



1.0 INTRODUCTION

Wai Kee (Zens) Construction & Transportation Co., Ltd. (WKC&T) has been awarded the Contract No.: CV/2002/11, "Construction of Jetty at Lung Kwu Chau" (the Project) by the CED. ETS-Testconsult Limited (ETL) has been commissioned as Environmental Team (ET) to carry out impact marine water quality monitoring at Lung Kwu Chau.

Under the requirements of Section 4 of Environmental Permit to Construct and Operate a Designate Project (EP-150/2002/A), EM&A programme as set out in the EM&A Manual is required to be implemented. In accordance with the EM&A manual, environmental monitoring of water quality, ecology and waste management is required for the Project.

The EM&A requirement is described in details in subsequent sections, including:

- Monitoring parameters;
- Action and Limit levels for all environmental parameters;
- Event-Action Plans;
- Environmental mitigation measures, as recommended in the project EIA study report;
- Environmental requirements in contract documents.

This monthly EM&A report summarizes the impact monitoring results and audit findings of the EM&A program during the reporting period from 09 October to 08 November 2003.

2.0 PROJECT INFORMATION

2.1 Background

To provide essential navigational aid for aircraft operating into and out of Hong Kong International Airport, a Doppler VHF Omni-directional Range and Distance Measuring Equipment (DVOR/DME) Station is being operated on Lung Kwu Chau. The existing jetty at Lung Kwu Chau is too small and the surrounding waters are too shallow to accommodate the vessels employed by Civil Aviation Department (CAD) for transporting equipment and personnel for servicing and maintaining the DVOR/DME. At present, the transportation relies heavily on helicopters, the operation of which is prohibited during night times and adverse weather conditions. In order that emergency repair work can be undertaken during such periods, CED has proposed to construct a proper jetty for berthing of marine vessels.

2.2 Project Location and Scope

The proposed site of the Project is located on the eastern coast of Lung Kwu Chau as shown in Figure 1. Lung Kwu Chau is situated within the gazetted Sha Chau and Lung Kwu Chau Marine Park. Due to the remoteness of the site, the island is uninhabited with no infrastructure other than the existing jetty and the DVOR/DME Station. Under the preliminary design, the scope of this Project comprises the following:

- Construction of a precast concrete blockwork jetty (10 m by 20 m) with a single berth;
- Construction of a concrete catwalk (approximately 22 m long);
- Dredging of an approach channel to a level of -2.5 mCD in front of the berth;
- Installation of miscellaneous facilities on the jetty, including lighting, navigation light, fendering, handrails, bollards, tide gauge, etc;
- Demolition of the existing jetty upon completion of the proposed jetty;
- Extension of an existing footpath.

2.3 Construction Programme

The Project is scheduled to commence in April 2003 for completion in December 2003. The Construction Programme is attached in Appendix E.



2.4 Project Organization and Management Structure

The organization chart with respect to the on-site environmental management and monitoring program are shown in Appendix A.

2.5 Contact Details of Key Personnel

The key personnel contact names and telephone numbers are shown in table 2.1.

Table 2.1 Contact Details of Key Personnel

Organization	Project Role	Name of Key Staff	Tel. No.	Fax No.
CED	Employer	Mr. T. S. Tsui	2762 5571	2714 2054
AUES	Independent Environmental Checker	Mr. Cliff Lam	2959 6059	2959 6079
WKC&T	Contractor	Mr. W. T. Ho	2548 3529	2548 5248
ETL	Contractor's Environmental Team	Mr C L Lau (Environmental Team Leader)	2946 7791	2695 3944

3.0 CONSTRUCTION PROGRESS IN THIS REPORTING MONTH

The site area of this project is shown in Figure 1.

A summary of the major construction activities undertaken in this monitoring month were:

- Placing of sub-base at jetty and catwalk;
- Setting of precast concrete pavings, precast footpath's footings and slabs;
- Demolition of old jetty;
- In-situ concreting of staircase;
- Copings and pavings;
- Construction of pillar boxes;
- Marine fitting and E&M installation;
- Placing of armour rock along catwalk.

The above construction activities are defined as "General Construction Activities".

The implementation of the corresponding mitigation measures is summarized in Table 3.1.

Table 3.1 Implementation of Environmental Mitigation Measures

Construction Activities	Environmental Mitigation Measures
General construction works	<ul style="list-style-type: none">• Remove the rubbish accumulated in the site regularly;• Provide good site practice (e.g. selection of quieter plant and working methods and reduction in number of plant operating in critical areas close to Dolphins' habitats) to limit noise emissions at source;• Keep good waste management.

4.0 MARINE WATER QUALITY MONITORING

4.1 Monitoring Locations

The marine water quality monitoring stations during the dredging works for the jetty and catwalk foundation and approach channel are shown in TS-2031. The co-ordinates of the marine water monitoring stations are listed in Table 4.1.



Table 4.1 Marine Water Quality Monitoring Stations

Station	Easting	Northing
M1	806244	827080
M2	806329	826408
M3	806235	826089
C1	806116	827618
C2	806034	825308

Control station C1 should be the upstream control station for all monitoring stations during mid-ebb and Control Station C2 should be the upstream control station for all monitoring stations during mid-flood.

4.2 Monitoring Parameters

Monitoring parameters listed in Table 4.2 shall be measured by the ET to ensure that any deteriorating water quality could be readily detected and timely action be taken to rectify the situation. Table 4.3 shows the other relevant water quality parameters to be recorded during the impact monitoring.

Table 4.2 Monitoring Parameters

In-situ measurement	Laboratory analysis
Dissolved Oxygen (mg/L)	Suspended solids (mg/L)
Turbidity (NTU)	

Table 4.3 Other relevant water quality parameters

Water Quality Parameters	
Tidal stages	Ambient Temperature (°C)
Water depth (m)	Marine Water Temperature (°C)
Monitoring time (hr:mm)	Dissolved Oxygen saturation (%)
Weather Condition	Salinity (ppt)

Note: pH is agreed by ET Leader, the Engineer and IE to be irrelevant to the Project.

4.3 Monitoring Frequency

The impact monitoring frequency of marine water quality during the dredging works for the jetty and catwalk foundation and approach channel is summarized in Table 4.4.

Table 4.4 Monitoring frequency of Impact Monitoring

Frequency	Monitoring Depth
3 days/week, 2 tides/day	Surface, middle and bottom

4.4 Monitoring Methodology and Equipment Used

Positioning of the monitoring stations

A hand-held digital Global Positioning System (GPS) was used to identify the designated monitoring stations prior to water sampling.

Water Depth measurement

A portable, battery-operated echo sounder was used for the determination of water depth at each designated monitoring station.

In-situ Water Quality Monitoring Equipment

All in-situ monitoring instruments were checked, calibrated and certified by a laboratory accredited under HOKLAS or any other international accreditation scheme before use, and subsequently re-calibrated at 3 monthly intervals or sometimes longer throughout all stages of the water quality monitoring.

Dissolved Oxygen (DO) and temperature measuring equipment

Portable, weatherproof DO-measuring meter with built-in salinity compensation (YSI model 95) was used in the impact monitoring. It can be capable for measuring:

- a dissolved oxygen level in the range of 0-20 mg/L and 0-200 % saturation; and
- a temperature of 0-45 degree Celsius

This type of DO-measuring meter has a membrane electrode with automatic temperature compensation complete with a 50-feet cable. Wet bulb calibration for a DO meter was carried out before measurement at each monitoring station.

Turbidity Measurement Instrument

Portable and weatherproof turbidity meter (HACH model 2100P) was used during impact monitoring. It has a photoelectric sensor capable of measuring turbidity between 0-1000 NTU. Response of the sensor was checked with certified standard Turbidity solutions before the start of measurement.

Salinity

A portable salinity meter capable of measuring salinity in the range 0-40 ppt (YSI Model 30M) was provided for measuring salinity of the water at each monitoring station. It was checked with standard 30 ppt Salinity solutions before the start of measurement.

Water Sampling and Sample Analysis

In-situ monitoring was carried out at three depths: 1 meter below water surface, at mid-depth and 1 meter above the seabed. If the water depth is less than 6 m, the mid-depth station shall be omitted and if the water depth is below 3 m, only the mid depth station shall be monitored.

A water sampler comprising a transparent PVC cylinder, with a capacity of not less than 2 litres, was lowered into the water body at the predetermined depth. The opening ends of the sampler were then closed accordingly and water samples were collected.

The sample container, made by high-density polythene, was rinsed with a portion of the water sample. The water sample was then transferred to the container, labelled with a unique sample ID and sealed with a screw cap. The water samples were stored in a cool box maintained at 4°C. The water samples were then delivered to a local HOKLAS-accredited laboratory (Environmental Laboratory, ETS-Testconsult Ltd, HOKLAS Registration No. 022) on the same day for analysis.

4.5 Quality Assurance (QA) / Quality Control (QC) results and Determination Limits

At each measurement/sampling depth, two consecutive measurements of dissolved oxygen (DO), dissolved oxygen saturation (DOS), turbidity and salinity were taken. For turbidity measurement, the sample was collected by using sampler and then transferred to the cell. The reading of turbidity of the sample was directly recorded from the Turbidimeter (HACH 2100P) after inserting the cell to the Turbidimeter. For DO, DOS and Salinity, duplicate measurements were performed by dropping the calibrated probes of the corresponding monitoring equipments to the designated depths of the water



column and taking readings after stabilized. The duplicate measurements were averaged if the difference was not greater than 25%.

The summary of laboratory testing method of Total Suspended Solids analysis was shown in Table 4.5.

Table 4.5 The summary of laboratory testing method of Total Suspended Solids

Laboratory Analysis	Testing Procedure	Method Detection Limit
Total suspended solids	In house method based on APHA 19 th ed 2540D	1.0 mg/L

Environmental Laboratory of ETS-Testconsult Ltd has quality assurance and quality control programs in accordance with HOKLAS requirement. For the QA/QC procedures, one QC sample, one duplicate sample and one sample spike of every batch of 20 samples were analysed. The QA/QC results are summarized in Appendix G.

4.6 Details of site Equipment used for In-situ measurement

Table 4.6 shows the equipment used for in-situ monitoring of water quality. The calibration certificates are attached in Appendix B1.

Table 4.6 Details Impact Monitoring Equipment (In-site measurement)

Parameter	Model	Date of Calibration / Performance Check	Due Date	Equipment No.
Coordinate of Monitoring stations	MLR GPS Navigator, SP24	-----	-----	EW/005/01*
Dissolved Oxygen (Saturation), Temperature	YSI Dissolved Oxygen Meter, YSI 95	30-09-2003	29-12-2003	EW/003/002 *
Turbidity	HACH Model 2100P Turbid Meter	23-08-2003	22-11-2003	ET/0505/004 #
Salinity	YSI Model 30M	18-09-2003	18-12-2003	EW/004/01#
Water Depth	EAGLE Strata 128 Sonar	-----	-----	EW/002/02

Remark: (*) indicates the instrument should be calibrated on use.

(#) indicates the instrument should be checked with standard solution before use.

4.7 Action and Limit Level

The water quality criteria, namely Action and Limit (A/L) levels, determined according to the baseline study carried out by ET are presented in the table below.

Table 4.7 Water Quality Action and Limit Levels

Parameter	Action Level	Limit Level
Dissolved Oxygen (DO), mg/L	<u>Surface & Middle</u> 4 mg/L <u>Bottom</u> 2.86 mg/L	<u>Surface & Middle</u> 4 mg/L <u>Bottom</u> 2 mg/L
Suspended Solids (SS), mg/L (Depth-averaged)	44 mg/L or 120% of the upstream control station's SS at the same tide on the same day	49 mg/L or 130% of the upstream control station's SS at the same tide on the same day
Turbidity, NTU (Depth-averaged)	37.4 NTU or 120% of the upstream control station's turbidity at the same tide on the same day	46.2 NTU or 130% of the upstream control station's turbidity at the same tide on the same day

4.8 Event-Action Plans

Event-Action Plans are presented in Appendix F.



4.9 Monitoring Duration and Period

In-situ measurement was carried out at both mid-flood and mid-ebb at each monitoring station on a sampling day. Table 4.8 shows the schedule for impact water quality monitoring at Lung Kwu Chau.

Table 4.8 – Time Schedule of Water Quality Monitoring at Lung Kwu Chau

09 October and 08 November 2003						
Sunday	Monday	Tuesday	Wednesday	Thursday	Friday	Saturday
				9 Oct	10	11
12	13	14	15	16	17	18
19	20	21	22	23	24	25
26	27	28	29	30	31	1 Nov
2	3	4	5	6	7	8

▼ = Water quality monitoring, ■ = Site inspection,

4.10 Marine Water Monitoring Results

The impact water quality measurement results are presented in Appendix B2.

The summary of marine water quality exceedances is shown in Table 4.9 and Table 4.10.

Table 4.9 Summary of Marine Water Quality Exceedances in this reporting month

Station	Exceedance Level	DO		Turbidity		SS	
		Flood	Ebb	Flood	Ebb	Flood	Ebb
C1	Action	0	0	0	0	0	0
	Limit	0	0	0	0	0	0
M1	Action	0	0	0	1	0	0
	Limit	0	0	0	0	0	0
M2	Action	0	0	0	0	0	0
	Limit	0	0	0	0	0	0
M3	Action	0	0	0	0	0	0
	Limit	0	0	0	0	0	0
C2	Action	0	0	0	0	0	0
	Limit	0	0	0	0	0	0
Total	Action	0	0	0	1	0	0
	Limit	0	0	0	0	0	0

Table 4.10 Daily Exceedance summary of marine water quality

09 October to 08 November 2003						
Sunday	Monday	Tuesday	Wednesday	Thursday	Friday	Saturday
				9 Oct	10	11
12	13	14	15	16	17	18
19	20	21	22	23	24	25
26	27	28	29	30	31	1 Nov
2	3 <u>Mid-ebb</u> One Exceedance (AL) in Turbidity (M1) but not work-related.	4	5 No exceedances in all WMP*	6	7 No exceedances in all WMP*	8

(^) indicates WMP = Water Monitoring Parameters

(*) indicates AL = Action Level and (#) indicates LL = Limit Level



According to the summary of marine water monitoring results, one exceedance of Action Level in Turbidity at Monitoring Station M1 at 03 November 2003 (mid-ebb) was recorded in this reporting month.

4.11 Explanation of Exceedance

Monitoring Date	Tide	Exceedance parameters	Station	Explanation	Implementation of Event and Action Plan
03/11/03	Mid-Ebb	Turbidity	M1	<p>During the marine water quality monitoring at 03/11/2003, ET found that the major construction works was demolishing existing pier. No visible foam, oil, grease, litter or other objectionable matter were observed near the monitoring stations. Comparing the monitoring results of the same tide, the turbidity at M1 was lower than 120% of upstream control station C1. Besides, the Turbidity result at monitoring station M2 which is closer to the existing pier was found lower than monitoring station M1 and within the Action and Limit Level. This concluded that the water quality impact due the construction works was low and did not cause adversely effect on water quality near the site. Therefore, the exceedance was not work-related.</p>	<p>After discussing with the IEC and the Contractor, it was concluded that no further mitigation measures should be taken since the exceedance was not works-related.</p>

5.0 ECOLOGY MONITORING

5.1 Introduction

According to the EM&A manual, there will be small loss of backshore vegetation and grass/shrubland due to the construction of footpath to the catwalk. At the same time, the construction works also cause impact on the marine dolphin habitat near the north and east coast of Lung Kwu Chau.

In order to minimize the impact to an acceptable level, the implementation schedule of the recommended ecological mitigation measures is developed and stated at the Appendix A of EM&A manual.

Implementation of these recommended mitigation measures will be monitored and audited during the construction stage.

5.2 Monitoring Procedure

During the weekly site inspection, ET monitored and audited the implementation of the recommended mitigation measures for terrestrial ecology and marine ecology following the site inspection checklist.

5.3 Monitoring Frequency and Schedule

Weekly site inspection for terrestrial ecology and marine ecology was carried by ET during the construction period. Four site inspections were undertaken in this reporting month.

5.4 Result and Observation

A summary of the implementation status of the mitigation measures for terrestrial ecology and marine ecology on site inspections is presented in Appendix C.

No disturbance to the terrestrial habitat and dolphin habitat due to construction work was observed in this reporting month.

6.0 ENVIRONMENTAL NON-CONFORMANCE

6.1 Summary of Exceedance of Action and Limit Level

One exceedance of Action Level in Turbidity at 03/11/2003 (mid-ebb) was recorded in this reporting month. Since the exceedance was not work-related, no further mitigation measures were required.



6.2 Summary of Environmental Complaints

No environmental complaints were received in this monitoring month.

6.3 Summary of Notification of Summons and Prosecution

There were no notification of summons respect to environmental issues registered in this month.

7.0 WASTE MANAGEMENT

7.1 Waste Management Audit

Waste management audit was carried out by the ET. A summary of the implementation status of the mitigation measures on waste management is presented in Appendix C.

7.2 Records of Waste Quantities

All types of wastes arising from the construction work are classified into the following:

- General refuses;
- Chemical waste;
- Construction & demolition (C&D) material.

The quantities of waste for disposal in this month are summarized in Table 7.1.

Table 7.1 Summary of Quantities of Waste for Disposal in this reporting month

Type of Waste	Quantity	Disposal Location
Dredged Materials (Contaminated) (m ³)	0	Nil
Dredged Materials (Uncontaminated) (m ³)	0	Nil
C&D Material (Inert) (m ³)	0	Nil
C&D material (Non-inert) (m ³)	3	Public Refuse Collection Point
General Refuse (m ³)	4	Public Refuse Collection Point
Chemical Waste (m ³)	0	Nil

8.0 ENVIRONMENTAL AUDIT

8.1 Site Inspection

Site inspections were carried out by the ET at 17, 24 and 31 October, and 07 November 2003. A summary of the implementation status of the mitigation measures on site inspections is presented in Appendix H.

8.2 Status of Environmental Licensing and Permitting

All permits/licenses obtained in this reporting month are summarized in Table 8.1.

Table 8.1 Summary of environmental licensing and permit status

Description	Permit No.	Valid Period		Section
		From	To	
Environmental Permit	EP-150/2002/A	29/04/03	---	Whole work site
Marine Dumping Permit	EP/MD/04-005	15/05/03	14/11/03	• Hopper barge and Motor tug
Construction Noise Permit	GW-TW0136-03	01/05/03	31/10/03	• One Derrick Barge (CNP 061) • One Tug boat (CNP 221)
Construction Noise Permit	GW-TW0367-03	01/11/03	30/04/03	• One Derrick Barge (CNP 061) • One Tug boat (CNP 221)



8.3 Implementation Status of Environmental Mitigation Measures

WKC&T has been implementing the required environmental mitigation measures according to Implementation of Mitigation Measures stated in the Appendix A of EM&A manual. A summary of the implementation status of the mitigation measures is presented in Appendix H. The following observations were made during site inspection:

Water Quality

- All vessels were kept tidy and no oil or other substances were washed overboard;
- No litter and loose objects, e.g. tools, were left lying around.

Terrestrial Ecology and Marine Ecology

- No damage of surrounding natural habitats was observed;
- No open fires were observed within the work site boundary;
- No disturbance to the dolphin habitat was observed.

Waste Management

WKC&T has been implementing most mitigation measures on waste management. The Contractor was reminded to provide more manpower to maintain good wash management, such as recycling of waste before disposal.

8.4 Recommendations on site inspection findings

Based on the site inspection findings, the recommendations are as below:

- Use quiet or 'silenced' plant equipment;
- Avoid the use of high-speed vessels where possible, or slow the high-speed vessels to under 10 knots which is the speed restriction for all marine traffic inside the Marine Park Boundary;
- Check the work site boundaries regularly to ensure that no damage occurs to surrounding natural habitats;
- Construction activities shall not cause foam, oil, grease, scum, litter or other objectionable matter to be present on the water within the site;
- Maintain good site practices and waste management at the site;

8.5 Implementation Status of Event and Action Plan

Since the exceedance of Action Level in Turbidity at 03/11/2003 (mid-ebb) was not work-related, no further mitigation measures were required.

8.6 Implementation Status of Environmental Complaint Handling

No written or verbal complaints had been received during this monitoring month.

8.7 Implementation of Notification of Summons and Prosecution

There was no notification of summons respect to environmental issues registered in this reporting month. No prosecutions related to environmental issues were received.

9.0 CONCLUSION

Impact monitoring of marine water quality was carried out at designated stations in accordance with the EM&A Manual in this reporting month.

One exceedance of Action level in Turbidity at 03/11/2003 (mid-ebb) was recorded in this reporting month. Since the exceedance was not work-related, no further mitigation measures were required.



According to the ET weekly site inspections and IE monthly site audit carried out this month, it indicated that site practices of the WKC&T were generally undertaken in an environmentally acceptable manner and the overall site environmental performance was satisfactory.

10.0 FUTURE KEY ISSUES

10.1 Upcoming EM&A Schedule

Dredging for approach channel were completed in the end of September 2003. Therefore, no marine water quality monitoring will be required in the coming months. Hence, only weekly site inspection should be carried out in the coming months.

10.2 Upcoming construction works schedule in the coming two months

The major construction works planned to be carried out in next month and their possible impact is tabulated (Table 10.1) for reference.

Table 10.1 – Construction Plan in the coming two month

Construction Work	Activities (proposed)
Jetty Construction	<ul style="list-style-type: none">• <i>Imprinted concrete surfacing;</i>• <i>Installing handrailing.</i>
Catwalk Construction	<ul style="list-style-type: none">• <i>Imprinted concrete surfacing,</i>• <i>Installing handrailing.</i>
Footpath Construction	<ul style="list-style-type: none">• <i>Cable ducting;</i>• <i>Installing handrailing</i>
Existing Pier	<ul style="list-style-type: none">• <i>Demolishing existing pier.</i>




東業德勤測試顧問有限公司
ETS-TESTCONSULT LIMITED

Appendix A

Organization Chart

Construction of Jetty at Lung Kwu Chau Organization Chart

Organization Chart





東業德勤測試顧問有限公司
ETS-TESTCONSULT LIMITED

Appendix B1

Calibration Certificates for Impact Monitoring Equipments



Internal Calibration Report of Turbidimeter

Equipment Ref. No. : ET/0505/004

Manufacturer : HACH

Model No. : 2100P

Serial No. : 951100009130

Date of Calibration : 23 August 2003

Calibration Due : 22 Nov. 2003

Data

4.95	54.8	850
0 - 10 NTU Gelex Vial	10 - 100 NTU Gelex Vial	100 - 1000 NTU Gelex Vial
4.96	53.9	541

The equipment complies * / does not comply * with the specified requirements and is deemed acceptable * / unacceptable * for use.

* Delete as appropriate

Calibrated by : Linda Lam

Approved by : [Signature]



Internal Calibration Report of Dissolved Oxygen Meter

Equipment Ref. No.	<u>EW/003/002</u>	Manufacturer	<u>YSI</u>
Model No.	<u>95</u>	Serial No.	<u>9730182 AP</u>
Date of Calibration	<u>30 Sept 2003</u>	Calibration Due Date	<u>29 Dec 2003</u>

Ref. No. of Reference Thermometer : ET/2403/01

Ref. No. of Potassium Dichromate : ET/0520/003/02

Temperature Verification

Temperature (°C)		
Thermometer reading		20.0
Meter reading		20.0

Linearity Checking

Purging time, min	DO meter reading, mg/L			Winkler Titration result, mg/L		
	1	2	Average	1	2	Average
2	7.11	7.09	7.10	7.03	7.04	7.04
5	5.28	5.30	5.29	5.32	5.33	5.33
10	2.67	2.71	2.69	2.67	2.65	2.66
Linear regression coefficient				0.9995		

Zero Point Checking

DO meter reading, mg/L	0.0
------------------------	-----

Salinity Checking

Salinity (ppt)	DO meter reading, mg/L			Winkler Titration result, mg/L		
	1	2	Average	1	2	Average
10	7.00	7.02	7.01	7.07	7.09	7.08
30	6.66	6.68	6.67	6.79	6.81	6.80

Acceptance Criteria

- (1) Difference between temperature readings from temperature sensor of DO probe and reference thermometer : < 0.5 °C
- (2) Linear regression coefficient : < 0.99
- (3) Zero checking: 0.0mg/L
- (4) Difference (%) of DO content from the meter reading and by winkle titration : ± 5%

The equipment complies * / does not comply * with the specified requirements and is deemed acceptable * / unacceptable * for use.

* Delete as appropriate

Calibrated by

Linda Law

Approved by :



Performance Check of Salinity Meter

Equipment Ref. No. : EW/004/01 Manufacturer : YSI

Model No. : 30 M Serial No. : 97 J0300AA

Date of Calibration : 18 Sept 2003 Due Date : 18 Dec. 2003

Ref. No. of Salinity Standard used (30ppt)

J137

Salinity Standard (ppt)	Measured Salinity (ppt)	Difference %
30	30.5	1.67

Acceptance Criteria

Difference : <10 %

The salinity meter complies * / ~~does not comply~~ * with the specified requirements and is deemed acceptable * / ~~unacceptable~~ * for use. Measurements are traceable to national standards.

Checked by : Tek

Approved by : Linda Law



東業德勤測試顧問有限公司
ETS-TESTCONSULT LIMITED

Appendix B2

Impact Monitoring Results

Date: 31-10-03

Mid-Flood										Turbidity (NTU)											
Station	Duration	Ambient Temp (°C)	Water Depth (m)	Water Temp (°C)	Salinity (ppt)				Dissolved Oxygen, DO (mg/L)				Dissolved Oxygen Saturation, DOS (%)				Turbidity (NTU)				
					S	M	B	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.	
C1	13:00-13:18	27°C, Sunny	14.8	26.5	26.0	25.5	25.6	25.6	26.5	26.5	26.5	26.9	26.9	26.9	5.94	5.96	5.96	5.64	5.72	5.68	
M1	12:38-12:56	27°C, Sunny	11.2	25.8	25.6	25.5	25.2	25.2	25.2	26.7	26.7	29.3	29.3	29.3	5.62	5.88	5.65	6.03	6.10	6.07	
M2	12:28-12:38	27°C, Sunny	7.1	25.6	25.5	25.4	25.1	25.1	25.1	26.4	26.4	26.1	28.1	28.1	28.1	6.02	6.06	6.04	5.84	5.92	5.83
M3	12:17-12:25	27°C, Sunny	3.6	25.9	—	25.7	27.9	27.9	—	—	—	28.4	28.4	28.4	6.10	6.04	6.07	—	—	—	
C2	12:05-12:15	27°C, Sunny	4.0	26.9	—	26.1	27.5	27.5	—	—	—	27.6	27.6	27.6	6.18	6.20	—	—	—	—	

Mid-Ebb										Turbidity (NTU)											
Station	Duration	Ambient Temp (°C)	Water Depth (m)	Water Temp (°C)	Salinity (ppt)				Dissolved Oxygen, DO (mg/L)				Dissolved Oxygen Saturation, DOS (%)				Turbidity (NTU)				
					S	M	B	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.	
C1	17:00-17:10	27°C, Sunny	4.8	25.5	—	25.2	27.4	27.4	—	—	27.5	27.5	27.5	5.64	5.72	5.68	—	—	5.68	5.42	5.48
M1	17:13-17:22	27°C, Sunny	5.1	25.4	—	25.4	26.5	26.5	—	—	29.2	29.3	29.3	5.71	5.76	5.74	—	—	5.74	5.52	5.58
M2	17:24-17:39	27°C, Sunny	8.1	26.1	25.0	25.0	26.1	26.1	27.3	27.3	27.3	29.4	29.4	29.4	6.10	6.04	6.07	5.85	5.92	5.89	
M3	17:42-17:55	27°C, Sunny	12.6	25.1	25.0	26.5	26.5	28.4	28.4	30.5	30.5	30.5	30.5	30.5	5.76	5.82	5.79	6.0	5.9	5.88	
C2	17:58-18:13	27°C, Sunny	15.5	25.1	25.1	25.0	25.8	25.8	28.1	28.1	30.0	30.0	30.0	6.22	6.24	6.23	6.1	6.09	6.16	5.98	6.02

Flood-Flood												Turbidity (NTU)												Suspended Solids, SS (mg/L)																													
Duration	Ambient Temp (°C) / Water Depth (m)	Water Temp (°C)				Salinity (ppt)				Dissolved Oxygen, DO (mg/L)				Dissolved Oxygen Saturation, DOS (%)				Depth (S.M.E.)				Ave. (S.M.E.)				Depth (S.M.E.)				Ave. (S.M.E.)																							
		S		M		B		S		M		B		S		M		B		S		M		B		S		M		B																							
		S	M	B	1st	2nd	Ave.	1st	2nd	Ave.	1st	2nd	Ave.	1st	2nd	Ave.	1st	2nd	Ave.	1st	2nd	Ave.	1st	2nd	Ave.	1st	2nd	Ave.	1st	2nd	Ave.	1st	2nd	Ave.																			
C1	16:41	24°C, Sunny	17.4	26.3	25.7	25.1	23.4	23.4	23.4	27.6	27.6	27.6	29.0	29.0	29.0	7.01	6.93	6.97	6.45	6.51	6.48	6.73	6.04	5.95	6.00	9.90	9.94	9.18	32.7	32.3	35.9	0.55	4.56	4.47	4.50	5.76	5.82	5.80	19.1	18.4	18.8	9.70	4.0	4.0	4.0	4.0	4.0	4.0	19	19	10		
M1	16:16	24°C, Sunny	15.2	26.2	25.7	25.2	24.0	24.0	24.0	28.0	28.0	28.0	29.5	29.5	29.5	6.71	6.53	6.67	6.11	6.03	6.07	6.37	5.90	5.82	5.86	9.55	9.51	9.47	36.5	36.5	34.6	83.7	84.2	83.92	3.96	3.90	7.31	7.20	7.30	24.1	23.2	23.7	11.6	3.8	4.0	3.9	7.0	7.0	7.0	21	22	11	
M2	16:02	24°C, Sunny	7.8	26.1	25.8	25.3	22.9	22.9	22.9	28.1	28.1	28.1	28.1	28.1	28.1	6.44	6.37	6.41	6.21	6.13	6.17	6.29	5.84	5.76	5.80	9.16	9.10	9.13	88.4	87.5	88.0	33.1	32.3	32.7	3.61	3.53	3.60	5.22	5.14	5.20	15.6	14.4	15.0	7.90	3.4	3.6	3.5	5.4	5.6	5.5	13	14	7.5
M3	15:50	24°C, Sunny	5.8	26.0	—	25.7	22.6	22.6	—	—	—	—	27.4	27.4	27.4	5.80	5.89	5.85	—	—	—	5.85	5.79	5.84	8.40	8.49	8.45	—	—	—	81.9	82.5	82.2	4.11	4.03	4.10	—	—	—	27.6	28.1	27.9	15.0	4.2	4.4	4.3	—	—	—	26	26	15	
C2	15:30	24°C, Sunny	5.0	26.5	—	25.0	24.6	24.6	—	—	—	—	27.2	27.2	27.2	7.90	7.81	7.86	—	—	—	7.86	7.44	7.32	7.36	11.47	11.36	11.42	—	—	—	106.5	105.6	106.1	3.91	3.82	3.90	—	—	—	19.6	18.7	19.3	11.6	3.6	3.4	3.5	—	—	—	18	18	11

Remark: The bolded data (Turbidity and Suspended Solids at all monitoring stations) exceeded Limit Level but not work-related after ET's investigation.

Date: 05-11-03

Mild-Flood												Severe-Flood																																										
Station	Duration	Ambient Temp (°C)			Water Temp (°C)			Salinity (ppt)			Dissolved Oxygen, DO (mg/L)			Dissolved Oxygen Saturation, DOS (%)			Turbidity (NTU)			Suspended Solids, SS (mg/L)																																		
		Weather Condition			Depth (m)			S			M			B			S			M			B																															
		S	M	B	1 st	2 nd	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.																													
C1	16:32-18:43	28°C, Clear	14.8	26.0	25.7	25.2	25.2	26.3	26.3	27.4	27.5	27.5	28.6	28.5	28.6	28.6	6.29	6.28	6.29	6.03	5.97	6.00	6.15	5.79	5.76	94.3	94.1	94.2	90.8	90.0	86.2	85.8	17.4	17.8	17.6	22.3	21.5	21.9	26.2	26.6	22.0	18	17	20	21	21	27	22						
M1	16:47-17:02	28°C, Clear	10.2	26.2	25.9	25.5	25.6	27.6	27.6	27.9	27.9	27.8	28.5	28.5	28.5	28.5	6.01	5.98	6.18	6.16	6.17	6.08	5.92	5.85	5.94	89.4	90.4	87.3	90.4	85.6	85.1	88.9	15.8	17.3	16.6	24.3	23.4	23.9	28.5	29.2	28.9	23.1	15	14	15	21	22	27	28	21				
M2	17:10-17:14	28°C, Clear	6.2	26.0	25.9	25.6	25.1	28.1	28.1	28.3	28.3	28.3	28.0	28.0	28.0	28.0	6.56	5.64	5.64	5.74	5.76	5.77	5.70	5.38	5.34	5.36	86.1	85.4	85.8	84.8	85.2	85.0	86.4	79.8	80.1	14.6	14.8	14.7	16.2	17.4	16.3	23.1	23.8	23.5	18.3	15	14	15	17	17	22	21	18	
M3	17:16-17:25	28°C, Clear	5.5	26.2	—	25.8	28.4	28.4	—	—	—	—	28.5	28.5	28.5	28.5	6.14	6.09	6.12	—	—	—	6.12	5.64	5.64	5.66	92.1	91.3	91.7	—	—	85.2	84.7	85.0	17.4	17.5	17.5	—	—	—	20.6	20.7	20.7	19.1	16	15	16	—	—	—	20	19	20	18
C2	16:17-16:24	28°C, Clean	5.8	26.3	—	25.9	27.8	27.8	—	—	—	—	28.2	28.2	28.2	28.2	6.37	6.32	6.45	—	—	—	6.35	5.81	5.84	5.83	95.4	94.7	95.1	—	—	87.4	87.8	87.6	19.3	18.8	19.1	—	—	—	22.7	21.9	22.3	20.7	20	21	21	—	—	—	20	21	21	21

Mid-Flood

四三

Date: 07-11-03

Solid-Flood

id	Flood	Duration	Ambient Temp (°C)	Water Depth (m)	Water Temp (°C)	Salinity (ppt)	Dissolved Oxygen Saturation, DO (mg/L)						Dissolved Oxygen Saturation, DOS (%)						Turbidity (NTU)						Suspended Solids, SS (mg/L)																										
							S			M			B			S			M			B			S			M			B																				
							S	M	B	1 st	2 nd	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.																					
C1	18:14-18:25	25°C / Sunny	26.7	26.4	26.3	25.8	25.8	26.0	26.0	27.0	27.0	27.0	7.95	7.98	7.92	7.54	7.58	7.79	6.98	6.90	6.84	11.90	11.94	11.25	11.16	11.21	10.26	10.18	10.22	11.2	10.1	10.7	8.42	8.36	8.40	18.2	17.6	17.9	12.3	11	10	11	7.6	7.4	7.5	15	16	16	11		
M1	17:34-18:10	25°C / Sunny	26.8	26.6	26.5	25.2	25.2	25.2	25.9	25.9	26.8	26.8	8.17	8.10	8.14	7.82	7.73	7.78	7.96	7.92	7.04	7.08	12.18	12.10	12.14	11.46	11.51	10.47	10.39	10.43	6.72	6.63	6.70	14.2	14.9	14.6	17.2	16.3	16.8	12.7	6.8	6.6	6.7	12	13	13	15	15	15	11	
M2	17:39-17:51	25°C / Sunny	26.7	26.5	26.3	24.9	24.9	24.9	24.9	24.9	24.9	24.9	8.40	8.32	8.36	8.05	7.96	8.01	8.19	7.85	7.56	7.61	12.53	12.43	12.49	11.89	11.80	11.85	11.25	11.16	11.21	5.71	5.62	5.70	6.25	6.15	6.20	5.58	5.47	5.50	5.80	4.6	4.6	4.7	5.8	6.0	5.9	5.3	5.3	5.3	5.3
MS	17:37-17:37	25°C / Sunny	5.6	26.8	—	26.3	25.1	25.1	25.1	—	—	25.7	25.7	8.21	8.13	8.17	—	—	8.17	7.31	7.23	7.27	12.24	11.16	11.70	—	—	—	10.75	10.67	10.71	6.72	6.62	6.70	—	—	11.1	10.2	10.7	8.70	8.62	8.60	6.1	—	—	10	10	10	8.1		
C2	17:45-17:25	25°C / Sunny	5.0	26.7	—	26.2	24.8	24.8	24.8	—	—	26.0	26.0	8.42	8.32	8.37	—	—	8.37	7.20	7.11	7.16	12.55	12.47	12.51	—	—	—	10.58	10.50	10.54	7.61	7.54	7.60	—	—	—	19.2	18.3	18.8	13.2	6.8	7.0	6.9	—	—	17	17	17	12	

Rückblick



Site ID	Ebb	Duration	Ambient Water Condition	Water Depth (m)			Salinity (ppt)			Dissolved Oxygen, DO (mg/l)			Dissolved Oxygen Saturation, DOS (%)			Turbidity (NTU)			Suspended Solids, SS (mg/l)																																							
				Temp (°C)			Water Temp (°C)			S			M			B			S			M			B																																	
				S	M	B	1 st	2 nd	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.	1 st	2 nd	Ave.																																		
C1	12:35-12:47	25°C / Sunny	26.5	26.4	26.2	27.3	27.3	27.3	28.0	28.0	28.4	28.4	28.4	28.4	28.4	28.4	6.22	6.22	6.73	6.78	7.00	6.26	6.17	6.22	106.8	106.0	106.4	100.2	99.4	99.8	92.1	91.3	91.7	14.0	13.2	13.6	17.8	16.9	17.4	26.1	25.4	25.8	18.9	13	13	16.1	17	17	24	23	24	18						
M1	12:30-12:45	25°C / Sunny	26.6	26.5	26.3	27.1	27.0	27.0	27.8	27.8	28.1	28.1	28.1	28.1	28.1	28.1	6.90	6.90	6.90	6.94	7.13	6.44	6.32	6.37	108.3	107.4	107.9	102.7	101.8	102.3	94.3	93.3	93.3	93.3	93.3	93.3	93.3	11.4	12.2	11.8	16.1	15.4	15.8	21.1	20.3	20.7	16.1	10	11	11	14	14	14	20	19	20	15	
M2	12:04-12:15	25°C / Sunny	26.4	26.5	26.5	27.0	27.0	27.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	7.52	7.52	7.57	7.57	7.48	7.11	7.03	7.07	108.4	108.9	109.3	107.0	107.9	107.4	111.2	111.2	111.7	111.7	104.6	103.7	104.2	9.71	9.63	9.67	14.4	13.5	14.0	22.4	21.5	22.0	15.2	8.8	9.0	8.9	13	13	12	13	19	20	14	
M3	11:53-12:02	25°C / Sunny	5.8	26.5	—	26.5	26.4	26.4	—	—	—	—	—	—	—	—	7.84	7.72	7.64	7.66	7.66	7.66	7.66	7.66	115.1	115.1	115.6	—	—	—	—	—	—	—	113.7	113.0	113.4	9.26	9.17	9.20	—	—	—	—	17.2	16.4	16.3	13.0	8.6	8.8	8.7	—	—	—	14	13	14	11
C2	11:40-11:50	25°C / Sunny	5.2	26.9	—	27.1	27.9	27.9	—	—	—	—	—	—	—	—	8.41	8.21	8.13	8.17	8.27	8.45	8.46	8.41	—	—	—	—	—	—	—	—	—	—	10.5	11.1	10.8	10.1	9.93	10.0	—	—	—	—	10.4	9.6	9.4	9.5	—	—	—	10	9.8	9.9	9.7			







東業德勤測試顧問有限公司
ETS-TESTCONSULT LIMITED

Appendix C

Graphical Plots of Impact Monitoring Data











Suspended Solids (Depth-average) at Mid-Flood Tide



Suspended Solids (Depth-average) at Mid-Ebb Tide





東業德勤測試顧問有限公司
ETS-TESTCONSULT LIMITED

Appendix D

Weather Condition during Impact Monitoring



Weather Condition

Date	Rainfall (mm)	Max. Temp (°C)	Min. Temp. (°C)	Relative Humidity (%)	Weather Condition
09/10/03	Trace	28.4	26.2	77	Cloudy
10/10/03	15.9	27.2	25.6	84	Cloudy
11/10/03	32.7	29.1	25.3	89	Rainy
12/10/03	Trace	29.6	26.2	82	Cloudy
13/10/03	Trace	29.7	24.3	79	Cloudy
14/10/03	-	24.3	20.7	68	Fine
15/10/03	-	23.3	19.9	69	Fine
16/10/03	-	26.3	22.0	64	Fine
17/10/03	-	25.8	22.0	68	Fine
18/10/03	-	25.9	22.6	67	Sunny
19/10/03	Trace	25.6	22.5	64	Cloudy
20/10/03	-	26.2	22.4	64	Sunny
21/10/03	-	27.0	22.7	68	Fine
22/10/03	-	26.8	23.1	72	Fine
23/10/03	-	26.1	23.0	71	Fine
24/10/03	-	25.7	22.8	74	Fine
25/10/03	-	26.4	22.0	64	Sunny
26/10/03	-	26.0	22.0	66	Sunny
27/10/03	-	26.2	22.7	74	Sunny
28/10/03	-	27.4	23.2	68	Fine
29/10/03	-	26.2	23.3	65	Fine
30/10/03	-	25.2	22.4	66	Fine
31/10/03	-	25.5	22.4	75	Sunny
01/11/03	-	26.9	22.6	78	Cloudy
02/11/03	-	28.6	23.1	75	Fine
03/11/03	-	29.6	24.4	56	Sunny
04/11/03	-	26.8	23.5	71	Fine
05/11/03	-	26.4	23.5	79	Fine
06/11/03	-	26.1	22.9	80	Sunny
07/11/03	Trace	27.1	24.5	82	Fine
08/11/03	32.7	25.2	23.0	92	Cloudy



東業德勤測試顧問有限公司
ETS-TESTCONSULT LIMITED

Appendix E

Construction Programme of the Project

2014											
Month	Activities	Description	Early Start	Early Finish	Actual Start	Actual Finish	April	May	June	July	August
1/01/2014	Commissioned		0	4 Apr 11	-	-	-	-	-	-	-
1/14/2014	Start Materials / tools		21	4 Apr 11	31 Mar 2013	4 Apr 11	18 Mar 13	-	-	-	-
2/10/2014	Building foundations		47	15 Apr 11	21 Mar 2013	18 Apr 11	18 Mar 13	-	-	-	-
2/21/2014	Brickwork - walls		211	21 Mar 2013	29 Dec 13	9 Jan 14	24 Aug 13	-	-	-	-
3/01/2014	Pest control treatments		73	50 Dec 13	26 Jan 14	-	-	-	-	-	-
3/10/2014	Heating & Electrical		15	21 Apr 11	21 May 2013	24 Apr 11	23 May 2013	-	-	-	-
3/20/2014	Dumping ground		23	25 Apr 11	22 May 2013	25 Apr 11	23 May 2013	-	-	-	-
3/27/2014	Site offices - proposal & approval		12	4 Apr 11	24 Apr 11	4 Apr 11	24 Apr 11	-	-	-	-
4/10/2014	Site offices - erection		29	25 Apr 11	22 May 2013	25 Apr 11	22 May 2013	-	-	-	-
4/20/2014	Project code & Information & support		11	25 Apr 11	11 May 2013	14 Jun 13	11 Jun 13	-	-	-	-
4/27/2014	Project code - feedback		15	18 May 2013	20 Jun 2013	31 Jul 13	4 Aug 13	-	-	-	-
5/09/2014	Block foundations & supports		11	25 Apr 11	29 May 2013	31 May 2013	14 Aug 13	21 Sep 13	-	-	-
5/16/2014	Earth - cut & fill (dry)		60	30 Apr 11	25 May 2013	25 May 2013	14 Sep 13	-	-	-	-
5/20/2014	Notch cutting for supports channels		123	1 May 2013	31 Aug 13	-	-	-	-	-	-
5/24/2014	Excavate		6	-	20 Dec 13	-	-	-	-	-	-
Sub Total											
6/01/2014	Building foundations		11	15 Apr 11	31 Mar 2013	3 Apr 11	11 Feb 13	27 Feb 13	-	-	-
6/10/2014	Brickwork - approach channel		20	1 Apr 11	20 Sep 13	23 Sep 13	24 Sep 13	-	-	-	-
6/21/2014	Total										
7/01/2014	Project Safety procedures		11	9 Nov 2013	18 Dec 2013	11 Dec 13	7 Dec 13	-	-	-	-
7/23/2014	1) Earth Work		10	14 Aug 13	28 Aug 13	16 Sep 13	6 Sep 13	-	-	-	-
8/01/2014	Chemical (d) treated jetty supports		4	11 Oct 13	31 Dec 2013	11 Sep 13	17 Sep 13	-	-	-	-
8/10/2014	Type I earthworks for jetty		5	21 Oct 13	24 Oct 13	-	-	-	-	-	-
Sub Total											
8/20/2014	Setting permanent blocks of paving to level - 1 Oct 2013		21	19 Dec 2013	9 Feb 2014	14 Feb 13	21 Aug 13	-	-	-	-
8/27/2014	Setting permanent blocks of paving to level 2nd fl		6	29 Aug 13	3 Sep 13	1 Aug 13	1 Aug 13	-	-	-	-
Sub Total											
9/01/2014	Walls		40	4 Aug 13	13 Oct 13	11 Aug 13	-	-	-	-	-
9/10/2014	Chem. (d) treated jetty		15	27 Oct 13	1 Nov 13	31 Oct 13	-	-	-	-	-
Sub Total											
9/21/2014	1) Paving 1st floor for car park		5	24 Oct 13	27 Oct 13	-	-	-	-	-	-
Sub Total											
9/30/2014	2) Paving 2nd floor for car park		10	1 Aug 13	11 Aug 13	12 Aug 13	20 Sep 13	-	-	-	-
10/01/2014	Building ground blocks of concrete - building (1 fl)		19	30 Dec 2013	8 Aug 13	7 Aug 13	4 Aug 13	-	-	-	-
10/10/2014	Setting ground blocks of concrete - building (1 fl)		1	4 Sep 13	10 Sep 13	7 Sep 13	4 Sep 13	-	-	-	-
10/10/2014	1) Paving 1st terrace		23	21 Sept 13	10 Oct 13	-	-	-	-	-	-
10/19/2014	1) Paving 1st terrace for car park		5	11 Oct 13	13 Oct 13	-	-	-	-	-	-
Sub Total											
10/21/2014	Building ground blocks of concrete - building (1 fl)		10	1 Aug 13	11 Aug 13	12 Aug 13	20 Sep 13	-	-	-	-
10/25/2014	Setting ground blocks of concrete - building (1 fl)		19	11 Aug 13	20 Sep 13	18 Sep 13	25 Sep 13	-	-	-	-
10/26/2014	Setting ground blocks of concrete - building (1 fl)		1	20 Aug 13	20 Sep 13	20 Aug 13	23 Sep 13	-	-	-	-
Sub Total											
10/27/2014	Plaster		19	21 Sep 13	15 Sep 13	3 Aug 13	-	-	-	-	-
10/28/2014	1) Paint concrete - exterior concrete		19	11 Oct 13	20 Oct 13	30 Oct 13	20 Sep 13	-	-	-	-
10/29/2014	2) Paint concrete - exterior concrete		1	1 Nov 13	20 Nov 13	4 Nov 13	-	-	-	-	-
Sub Total											
10/30/2014	1) Paint concrete - interior concrete		15	1 Nov 13	20 Nov 13	4 Nov 13	-	-	-	-	-
Sub Total											
10/31/2014	2) Paint concrete - interior concrete		37	6 Nov 13	5 Dec 13	-	-	-	-	-	-
11/01/2014	Exterior for foundations (1 fl set)		10	11 Nov 13	10 Nov 13	10 Nov 13	16 Dec 13	-	-	-	-
11/02/2014	Interior for foundations (1 fl set)		144	24 Nov 13	11 Dec 13	11 Dec 13	16 Dec 13	-	-	-	-
Sub Total											
11/03/2014	Walls		15	21 Nov 13	21 Nov 13	21 Nov 13	1 Dec 14	-	-	-	-
Sub Total											
11/04/2014	Paint base and roof		21	25 Oct 13	11 Nov 13	11 Nov 13	16 Dec 13	-	-	-	-
11/05/2014	Lighting - building		15	21 Nov 13	1 Dec 14	1 Dec 14	1 Dec 14	-	-	-	-
Sub Total											
11/06/2014	Lighting - exterior & car park		6	1 Dec 13	11 Dec 13	11 Dec 13	16 Dec 13	-	-	-	-
Sub Total											
11/07/2014	Demolition of old dry		15	18 Dec 13	24 Dec 13	24 Dec 13	18 Dec 13	-	-	-	-



東業德勤測試顧問有限公司
ETS-TESTCONSULT LIMITED

Appendix F

Event-Action Plans

Event and Action Plan for Marine Water Quality

Event	ET Leader	ER	Contractor
Action level being exceeded by one sampling day	<ul style="list-style-type: none"> • Repeat <i>in situ</i> measurement on next day of exceedance to confirm findings; • Identify source(s) of impact; • Inform Contractor and ER; • Check monitoring data, all plant, equipment and Contractor's working methods. 	<ul style="list-style-type: none"> • Check monitoring data submitted by ET and Contractor's working methods; • Confirm receipt of notification of non-compliance in writing; • Notify Contractor. 	<ul style="list-style-type: none"> • Inform the ER and confirm notification of the non-compliance in writing; • Rectify unacceptable practice; • Amend working methods if appropriate.
Action level being exceeded by two or more consecutive sampling days	<ul style="list-style-type: none"> • Repeat measurement on next day of exceedance to confirm findings; • Identify source(s) of impact; • Inform Contractor, ER and EPD; • Check monitoring data, all plant, equipment and Contractor's working methods; • Discuss mitigation measures with ER and Contractor; • Ensure mitigation measures are implemented; • Increase the monitoring frequency to daily until no exceedance of Action level. 	<ul style="list-style-type: none"> • Check monitoring data submitted by ET and Contractor's working methods; • Discuss with ET and Contractor on the proposed mitigation measures; • Ensure mitigation measures are properly implemented; • Assess the effectiveness of the implemented mitigation measures. 	<ul style="list-style-type: none"> • Inform the Engineer and confirm notification of the non-compliance in writing; • Rectify unacceptable practice; • Check all plant and equipment and consider changes of working methods; • Submit proposal of additional mitigation measures to ER within 3 working days of notification and discuss with ET and ER; • Implement the agreed mitigation measures.

Event and Action Plan for Marine Water Quality

Event	ET Leader	ER	Contractor
Limit level being exceeded by one sampling day	<ul style="list-style-type: none"> • Repeat measurement on next day of exceedance to confirm findings; • Identify source(s) of impact; • Inform Contractor, ER and EPD; • Check monitoring data, all plant, equipment and Contractor's working methods; • Discuss mitigation measures with ER and Contractor. 	<ul style="list-style-type: none"> • Check monitoring data submitted by ET and Contractor's working method; • Confirm receipt of notification of failure in writing; • Discuss with ET and Contractor on the proposed mitigation measures; • Request Contractor to review the working methods. 	<ul style="list-style-type: none"> • Inform the ER and confirm notification of the non-compliance in writing; • Rectify unacceptable practice; • Check all plant and equipment and consider changes of working methods; • Submit proposal of mitigation measures to ER within 3 working days of notification and discuss with ET and ER.
Limit level being exceeded by two or more consecutive sampling days	<ul style="list-style-type: none"> • Repeat measurement on next day of exceedance to confirm findings; • Identify source(s) of impact; • Inform Contractor, ER and EPD; • Check monitoring data, all plant, equipment and Contractor's working methods; • Discuss mitigation measures with ER and Contractor; • Ensure mitigation measures are implemented; • Increase the monitoring frequency to daily until no exceedance of Limit level for two consecutive days. 	<ul style="list-style-type: none"> • Check monitoring data submitted by ET and Contractor's working method; • Discuss with ET and Contractor on the proposed mitigation measures; • Request Contractor to critically review the working methods; • Make agreement on the mitigation measures to be implemented; • Ensure mitigation measures are properly implemented; • Consider and instruct, if necessary, the Contractor to slow down or to stop all or part of the construction activities until no exceedance of Limit level. 	<ul style="list-style-type: none"> • Take immediate action to avoid further exceedance; • Submit proposal of mitigation measures to ER within 3 working days of notification and discuss with ET and ER; • Implement the agreed mitigation measures; • Resubmit proposals of mitigation measures if problem still not under control; • As directed by the Engineer, to slow down or to stop all or part of the construction activities until no exceedance of Limit level.



東業德勤測試顧問有限公司
ETS-TESTCONSULT LIMITED

Appendix G

QA/QC Results of Laboratory Analysis



QA/QC Results of Laboratory Analysis of Total Suspended Solids

Sampling Date	QC Sample Analysis	Sample Duplicate		Sample Spike	
		% Recovery *	Sample ID	% Error #	Sample ID
31/10/2003	96.7	FM1S	6.9	FC1S	102.0
	107.4	FC1M	-7.4	EM2S	98.0
	100.6	EM2B	0.0	EC2B	102.0
03/11/2003	106.6	FM1S	-5.1	FC1S	94.1
	95.1	FC1M	3.4	EM2S	103.8
	101.7	EM2B	-2.2	EC2B	101.9
05/11/2003	97.9	FM1S	6.9	FC1S	97.9
	102.5	FC1M	-4.9	EM2S	96.0
	105.4	EM2B	-4.7	EC2B	102.0
07/11/2003	97.5	FM1S	3.0	FC1S	95.8
	102.1	FC1M	2.7	EM2S	98.1
	97.3	EM2B	-5.1	EC2B	93.9

Note: (*) % Recovery of QC Sample should be between 80% to 120%.

(#) % Error of Sample Duplicate should be between -10% to 10%.

(@) % Recovery of Sample Spike should be between 80% to 120%.



東業德勤測試顧問有限公司
ETS-TESTCONSULT LIMITED

Appendix H

Summary of the Implementation Status of Mitigation Measures

SUMMARY OF IMPLEMENTATION STATE OF THE MITIGATION MEASURES

Environmental Protection Measures / Mitigation Measures	Implementation Stages*			Remark
	Yes	No	N/A	
Measures to be implemented during dredging:				
• Use of a closed grab dredger with a maximum daily production rate of 500 m ³ /day;			✓	No dredging activities.
• Deployment of silt curtain to enclose the grab while dredging works are in progress. The silt curtain shall be frame type and designed to enclose local pollution caused by the grab dredging.			✓	No dredging activities.
• The second layer of silt curtain shall be formed from tough, abrasion-resistant permeable membranes, supported on floated booms in such a way as to ensure that egress of turbid waters from the enclosed dredging area shall be restricted.		✓		No dredging activities.
• Use of small sized hopper barge and dredger for dredging works. The maximum draft of the dredger and hopper barge, when fully loaded, shall not exceed 2m. The hopper barge shall make more frequent trips to transport the dredged material to the allocated marine disposal ground, instead of remaining at Lung Kwu Chau until it is fully loaded, in order to avoid grounding of the barge during low tide.		✓		No dredging activities.
• Mechanical grabs shall be designed and maintained to avoid spillage and sealed tightly while being lifted.			✓	No dredging activities.
• All pipe leakages shall be repaired promptly and plant shall not be operated with leaking pipes.			✓	No dredging activities.
• The decks of all vessels shall be kept tidy and free of oil or other substances that might be accidentally or otherwise washed overboard.		✓		No dredging activities.
• Adequate freeboard (i.e. minimum of 200mm) shall be maintained on barges to ensure that decks are not washed by wave action.		✓		No dredging activities.
• All hopper barges and dredgers shall be fitted with tight fitting seals to their bottom openings to prevent leakage of material.			✓	No dredging activities.
• Construction activities shall not cause foam, oil, grease, scum, litter or other objectionable matter to be present on the water within the site or dumping grounds.			✓	No dredging activities.
• Loading of barges and hopper barges shall be controlled to prevent splashing of material into the surrounding water. Barges or hopper barges shall not be filled to a level that will cause the overflow of materials or sediment laden water during loading or transportation.		✓		No dredging activities.



SUMMARY OF IMPLEMENTATION STATE OF THE MITIGATION MEASURES

Environmental Protection Measures / Mitigation Measures	Implementation Stages*			Remark
	Yes	No	N/A	
Measure to be implemented during Demolition and removal works				
• Demolition and removal works of the submerged portion of the existing jetty shall be carried out around low tide to minimize the duration of works taking place within the marine waters.	✓			
Mitigation for terrestrial ecology				
• Check the work site boundaries regularly to ensure that no damage occurs to surrounding natural habitats.	✓			
• Prohibit and prevent open fires within the work site boundary during construction and provide temporary fire fighting equipment in the work areas.	✓			
• Reinstate temporary work sites/disturbed areas immediately after completion of the construction.	✓			
General mitigation for Chinese White Dolphin				
• The use of high-speed vessels in the construction or operation of the jetty shall be avoided where possible. If high-speed vessels must be used, they shall be required to slow to under 10 knots which is the speed restriction for all marine traffic inside the Marine Park Boundary. Furthermore, marine traffic entering the Marine Park to the proposed jetty area shall follow a regular and predictable route.	✓			
• All vessel operators working on the project shall be given a briefing, alerting them to the conservation significance of the Marine Park and the presence of dolphins in the area, and setting out guidelines for safe vessel operations around cetaceans.	✓			
• A policy of no dumping of rubbish, food, oil, or chemicals shall be strictly enforced. This shall also be covered in the contractor briefing.	✓			
• Before dredging, an exclusion zone of 500m radius shall be scanned around work area for at least 30 minutes prior to the start of dredging. If dolphins are observed in the exclusion zone, marine works shall be delayed until they have left the area. Furthermore, if dolphins enter the exclusion zone after dredging has commenced, marine works shall cease until they have left the area.		✓		No dredging activities.
• Staff shall monitor for the presence of dolphins within the exclusion zone by scanning the sea both with and without binoculars whilst positioned at vantage point near the summit of the hill behind the jetty location. The vantage point shall enable an extensive view of the 500m exclusion zone in all directions around the jetty. Staff shall communicate with the Engineer via a dedicated telecommunications device (e.g. mobile phone or 'walkie-talkie').	✓	✓		No dredging activities.

SUMMARY OF IMPLEMENTATION STATE OF THE MITIGATION MEASURES

Environmental Protection Measures/Mitigation Measures	Implementation Stages*			Remark
	Yes	No	N/A	
<i>Mitigation for minimising possible noise impacts on dolphins</i>				
• Other measures recommended to mitigate noise impact on dolphins by allowing their acclimatization to noise disturbance are to, as far as practicable:				
- The number of work vessels and small craft shall be minimised during the construction phase.				
- Dredging and jetty construction activities shall be continuous without short breaks or unpredictable noise outbursts at random intervals.	✓			
- Events shall be scheduled on a regular basis with similar activities planned for similar time period each day.	✓			
- Furthermore, the Contractor shall use quiet or 'silenced' plant equipment. All site plant equipment shall be well maintained.	✓			
• Removal of the existing jetty structure shall be done in a way that minimise noise impact on dolphins by following the above recommended measures. Blasting shall not be permitted. Silenced breakers shall be used and demolition and removal works of the submerged portion of the jetty shall be carried out around low tide to minimise transmittance of noise into the water. In addition, demolition of the jetty structure shall be planned so that, as far as practicable, the structure is 'cut' into large manageable sections to minimise the amount of time breakers are used.	✓			
• During the operational phase, vessels moored at the jetty for extended periods shall, as far as practicable, turn off their engines to minimise unnecessary underwater noise.	✓			
<i>Marine Sediment</i>				
• The material must be dredged, transported and disposed of in a manner which minimizes the loss of contaminants either into solution or by resuspension. During transportation and disposal of the dredged marine sediments, the following measures shall be taken to minimise potential impacts on water quality.				No dredging activities.
• Bottom opening of barges shall be fitted with tight fitting seals to prevent leakage of material. Excess material shall be cleaned from the decks and exposed fittings of barges and hopper dredgers before the vessel is moved.				No dredging activities.
• Monitoring of the barge loading shall be conducted to ensure that loss of material does not take place during transportation. Transport barges or vessels shall be equipped with automatic self-monitoring devices as specified by the Director of Environmental Protection.	✓			No dredging activities.



SUMMARY OF IMPLEMENTATION STATE OF THE MITIGATION MEASURES

Environmental Protection Measures/Mitigation Measures	Implementation Stages*			Remark	
	Yes	No	N/A		
Good Site Practices and Waste Reduction Measures					
Good site practices during the construction activities include:					
<ul style="list-style-type: none"> • Nomination of an approved personnel, such as a site agent, to be responsible for good site practices, arrangements for collection and effective disposal to an appropriate facility, of all wastes generated at the site. • Training of site personnel in proper waste management procedures. • High standards of waste management shall be observed on the works vessels and barges to ensure that no waste arisings or fuel/diesel oils are disposed to the surrounding marine waters. • No C&D materials and machinery fuels enter the marine waters at the site; • No stockpiles of construction material shall be permitted on Lung Kwu Chau Island. • All wastes, unused construction materials and construction equipment shall be removed from Lung Kwu Chau Island after the works are completed. • A recording system for the amount of wastes generated, recycled and disposed of (including the disposal sites). • In order to monitor the disposal of C&D materials at public filling areas, and to control fly-tipping, a trip-ticket system shall be included as one of the contractual requirements. 	✓			✓	
Waste reduction					
Waste reduction is best achieved at the planning and design stage, as well as by ensuring the implementation of good site practices. Recommendations to achieve waste reduction include:					
<ul style="list-style-type: none"> • Prior to disposal of C&D waste, it is recommended that wood, steel and other metals shall be separated for re-use and / or recycling to minimise the quantity of waste to be disposed of to landfill. • Proper storage and site practices to minimise the potential for damage or contamination of construction materials. • Plan use of construction materials carefully to minimise amount of waste generated and avoid unnecessary generation of waste. 	✓	✓		✓	



東業德勤測試顧問有限公司
ETS-TESTCONSULT LIMITED

Figures

Construction of Lung Kwu Chau Jetty

NOTES

1. All dimensions are in metres.
2. All co-ordinates refer to Hong Kong geodetic datum 1980 and are in metres.
3. All levels refer to chart datum (C.D.) and are in meters.

Environmental Permit No.:

EP-150/2002

Figure 1

CE

